

# Varistor

# Material Data Sheet

<b>Product Class:</b>	<b>Housed varistor B722xxT*</b>
<b>Date</b>	<b>30.09.2019</b>
IMDS ID if available	
<b>Version</b>	<b>5.06</b>

Product Part (IMDS: semi component)	Material Class (IMDS: Material)	Material (Classification) VDA 231	Substance	TMPS** [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
Active Part	Ceramic	3B	ZnO	91	1314-13-2	43,0	
			Bi2O3	4,0	1304-76-3		
			Sb2O3	2,5	1309-64-4		
			Co3O4	1	1308-06-1		
			NiO	0,5	1313-99-1		
			others*)	1			
Termination	Composite	4D	Cu or Ag	95	7440-50-8 7440-22-4	0,6	
			Glass frit (boro-silicate)	5			
High melting point solder	Heavy Metal	1C8	Sn Ag Cu	96,5 3 0,5	7440-31-5 7440-22-4 7440-50-8	1,2	
Low melting point solder	Heavy Metal	1C8	Sn Bi	42 58	7440-31-5 7440-69-9	0,2	
Leads	Heavy Metal	1C12	Cu	100	7440-50-8	6,0	
		1C8	Sn	100	7440-31-5	0,2	
Spring	Heavy Metal	1C12	Cu Sn P	92,75 7,0 0,25	7440-50-8 7440-31-5 7723-14-0	3,2	
		1C8	Sn	100	7440-31-5	0,2	
Encapsulation	Duromer	2D Halogen-free coating	SiO2 Epoxy Pyromellitic dianhydride Phosphated epoxy others*)	46 40 6,5 5 2,5	60676-86-0 25036-25-3 89-32-7	7,9	
Plastic housing inner cover	Thermoplastic	2A	Aromatic Liquid Crystal Polymer (LCP) Glass fiber others*)	68 30 2	147310-94-9	12,8	
Plastic housing outer cover	Thermoplastic	2A	Poly butylene terephthalate (PBT) Glass fiber Brominated flame retardant 1 Brominated flame retardant 2 Sb2O3 Other*)	68 16,2 6 6 3 0,8	24968-12-5 65997-17-3 68928-70-1 71342-77-3 1309-64-4	24,7	
<b>Sum in total:</b>						<b>100</b>	

sizes L x W [mm]	weight range [g]	material number	part numbers	sizes L x W [mm]	weight range [g]	material number	part numbers
21,6 X 17	3,8-5,5	B72214T*	T14K130-K420*	26 X 22	5,8-8,8	B72220T*	T20K50-K420*
				27,5 X 27,5	9,9-18,0	B72220T	T20K460-K1000*

**Not part of a Product Class** T20K50DF (B72220T0500K105) and T20K510M10K4 (B72220T0511K109) is not a part of this product class.

# Varistor

# Material Data Sheet

<b>Product Class:</b>	<b>Housed Varistor B722xxT*</b>
<b>Date</b>	<b>30.09.2019</b>
IMDS ID if available	
<b>Version:</b>	<b>5.06</b>

<b>Contact</b>	Mr. Christoph Ronner	<b>Important remarks:</b>  1) The declaration limit is 0.1% as defined by IEC 62474 (IEC PAS 61906). Traces are product parts, substances etc. that are below a percentage of 0.1 % by weight, if not otherwise regulated.  2) This Material Data Sheet contains typical values of the respective products set forth herein. We expressly point out that all values and statements contained herein are based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. TDK ELECTRONICS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE.
<b>Division</b>	PPD Q QM	
<b>Address</b>	8530 Deutschlandsberg, AUSTRIA	
	Tel: +43 3462 800 2139    mailto: functional.ppd-eqpm.db@tdk-electronics.tdk.com	
*) others: (not declarable or prohibited substances acc. GADSL) **) typical mass percentage of substance		

**The products set forth herein are "RoHS-compatible".** RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8<sup>th</sup>, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

**RoHS - Exemptions for the Product Class / Product according to Annex III: (  valid  not valid )**

- no exemptions;**
- Exemption 6 (a): Lead as an alloying element in steel for machining purposes and in galvanized steel containing up to 0,35 % lead by weight;
- Exemption 6 (b): Lead as an alloying element in aluminium containing up to 0,4 % lead by weight;
- Exemption 6 (c): Copper alloy containing up to 4 % lead by weight;
- Exemption 7 (a): Lead in high melting temperature type solder (i.e. lead-based alloys containing 85 % by weight or more lead);
- Exemption 7 (c)-I: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectric devices, or in a glass or ceramic matrix compound;
- Exemption 7 (c)-II: Lead in dielectric ceramic in capacitors for a rated voltage of 125 V AC or 250 V DC or higher;
- Exemption 7 (c)-III: Lead in dielectric ceramic in capacitors for a rated voltage of less than 125 V AC or 250 V DC;
- Exemption 15: Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages;
- Other Exemption than above .....